



PLS series item

SPECIFICATIONS
 Current Rating: 3Amps
 Insulation Resistance: 1000MΩ min
 Withstanding Voltage: 1000VAC
 Contact Resistance: 20mΩ max
 Operating Temperature: -40° C to +105° C
 Standard: PBT
 Contact Material: Iron or Alloy
 Contact Plating: Au or Sn Over Ni
 Max. Processing Temp: 180°C for 30-60 second
 (200°C for 10 second)



Shenzhen Rui Chi electronic Co., Ltd
 Office Address: Huaqiang Square D 8A Huaqiang North Futian District
 Shenzhen city Guangdong province.
 Tel : +86 -0755-23956133 83553465 23956122
 Fax: +86 -0755-23956133

No. of	DIN. A	DIN. B	No. of	DIN. A	DIN. B	No. of	DIN. A	DIN. B	No. of	DIN. A	DIN. B
1	0.00	2.54	11	25.40	27.94	21	50.80	53.35	31	76.20	78.74
2	2.54	5.08	12	27.94	30.48	22	53.35	55.88	32	78.74	81.28
3	5.08	7.62	13	30.48	33.02	23	55.88	58.42	33	81.28	83.82
4	7.62	10.16	14	33.02	35.56	24	58.42	60.96	34	83.82	86.36
5	10.16	12.70	15	35.56	38.10	25	60.96	63.50	35	86.36	88.90
6	12.70	15.24	16	38.10	40.64	26	63.50	66.04	36	88.90	91.44
7	15.24	17.78	17	40.64	43.18	27	66.04	68.58	37	91.44	93.98
8	17.78	20.32	18	43.18	45.72	28	68.58	71.12	38	93.98	96.62
9	20.32	22.86	19	45.72	48.26	29	71.12	73.66	39	96.62	99.06
10	22.86	25.40	20	48.26	50.80	30	73.66	76.20	40	99.06	101.6

UNLESS OTHEWIXE SPECIFIED TOLERANCE
 X : ±0.3 X° : ±5°
 X.X : ±0.2 X.X° : ±1°
 X.XX : ±0.2 X.XX° : ±0.5°

DRAWM NAME: CH-254-PH-1-XX-S-112-Ni-A
 SIZE A4 SCALE N:1 PROUCT
 REV A UNIT mm PROJECT PAGE 1/1

CHECKED LIU SHENG HUI DATE 05/28 CHECKED DATE /